

Electro-Replacement Ltd 1 Moor Park Industrial Centre, Tolpits Lane, Watford, Hertfordshire, WD18 9EU

ISO 3 Pole

Isolator Switch

Efficiently designed 3-pole weather proof isolator switch for safety, durability, and optimum performance.

Features:

- Voltage Compatibility: Up to 415V, suitable for single or 3-phase + neutral.
- Amperage: Designed for equipment isolation up to rated amps (20A / 35A).
- Base Mechanism: Provides easy termination with ample wiring space.
- **Connector Bars:** Fixed earth and neutral ensure secure cable clamping.
- **Cable Insertion:** Unscrew caps for 4x 25mm top/bottom knockouts and 2x 20mm adapters.
- Safety Caps: Insulating design for added protection.
- Lock Feature: Isolators can lock in the off position.
- Durability: Impact-resistant polycarbonate enclosure for robust protection.
- **Seal:** Weatherproof seal ensures resilience against external factors.
- Design: Heavy-duty suitable for both indoor and outdoor use.
- Protection Rating: IP66 Protects from dust, oil, water jets, and accidental contact.
- **Knockouts:** 4x 25mm top/bottom and 2x 20mm adapters included.

Order Details:

Product Code	Amps
ISO203E/N	20A
ISO353E/N	35A



TECHNICAL DATA	ISO 3 Pole
Size	85mm (W) x 170mm (H) x 90mm (D)
Colour	Grey, yellow & red
Knockouts	4 x knockouts to rear (20mm) • 4 x screw-out cable entries - 2 top + 2 bottom (25mm)
Wall Mountable	Yes
Lockable	Lockable in OFF position
IP Rating	IP66
Included	Fixing kit & instructions
Weight	0.45kg
Inner Carton Quantity	1
Standards	BS EN 60947-3

Technical SupportSales01923 220 27701923 255 344technical@electroreplacement.comsales@electroreplacement.com